

Open Infrastructure - Task #7482

On Alpine Linux the monit job for node-exporter uses the wrong path

12/15/2019 11:01 PM - Nico Schottelius

Status:	Closed	Start date:	12/15/2019
Priority:	Normal	Due date:	
Assignee:	Timothée Floure	% Done:	0%
Category:		Estimated time:	0.00 hour
Target version:			
PM Check date:			
Description			
Current state is:			
<pre>[22:56] router2.place5:/etc/monit# cat conf.d/node-exporter check process prometheus-node-exporter with pidfile /var/run/prometheus/prometheus-node-exporter.p id start program = "/etc/init.d/prometheus-node-exporter start" with timeout 60 seconds stop program = "/etc/init.d/prometheus-node-exporter stop" [22:56] router2.place5:/etc/monit#</pre>			
However the init script is /etc/init.d/node-exporter.			
Add an "os" check into manifest/dcl in the router section to use a different __ungleich_monit config depending on the OS.			
MR for this one not direct push, please			

History

#1 - 12/16/2019 10:07 AM - Timothée Floure

Add an "os" check into manifest/dcl in the router section to use a different __ungleich_monit config depending on the OS.

Wouldn't it be better to add this check to the `__ungleich_monit` type, which generate the `/etc/monit/conf.d/node-exporter` file?

#2 - 02/24/2020 10:23 AM - Timothée Floure

- Status changed from New to In Progress

#3 - 02/24/2020 10:55 AM - Timothée Floure

https://code.ungleich.ch/ungleich-intern/dot-cdist/merge_requests/67

#4 - 02/24/2020 11:24 AM - Timothée Floure

- Status changed from In Progress to Closed