Open Infrastructure - Task #7625

Manually fix consul+node_exporter on new router1.place6

01/18/2020 01:02 PM - Nico Schottelius

Status: Start date: Rejected 01/18/2020 **Priority:** Normal Due date: Nico Schottelius % Done: Assignee: 0% **Estimated time:** 0.00 hour Category: Target version: PM Check date:

Description

```
[13:01] router1.place6:~# /etc/init.d/consul start
/etc/init.d/consul: .: line 39: can't open '/lib/lsb/init-functions': No such file or directory
[13:02] router1.place6:~# /etc/init.d/consul.apk-new start
  * Checking /etc/consul ...
Config validation failed: Multiple private IPv4 addresses found. Please configure one with 'bind'
and/or 'advertise'.
        [ !! ]
  * checkpath: owner `consul.apk-new:consul.apk-new' not found
  * ERROR: consul.apk-new failed to start
[13:02] router1.place6:~#
```

Follow up

- No init script deployment on alpine
- · Modify data dir
- Different configuration directory on alpine
- · Should use the new interface template go syntax, however it did not work on testing

History

#1 - 01/18/2020 01:03 PM - Nico Schottelius

- Description updated

#2 - 01/18/2020 01:26 PM - Nico Schottelius

Use alpine's init script:

```
[13:02] router1.place6:~# mv /etc/init.d/consul.apk-new /etc/init.d/consul
[13:03] router1.place6:~# cat /etc/conf.d/consul
# Consul startup
consul_opts="agent -config-dir=/etc/consul"
[13:04] router1.place6:~#
```

[13:06] router1.place6:/etc/consul# /etc/init.d/consul start

Changing path to what we used on debian

* Checking /etc/consul \dots

04/25/2024 1/3

```
Config validation failed: Multiple private IPv4 addresses found. Please configure one with 'bind' and/or 'adve
rtise!.
                                                                                                  [!!]
* Starting consul ...
                                                                                                  [ ok ]
[13:06] router1.place6:/etc/consul# cat conf.d/config.json
   "data_dir": "/var/lib/consul"
   ,"bind_addr": "2a0a:e5c0:2:15::5"
   ,"client_addr": "2a0a:e5c0:2:15::5 ::1 127.0.0.1"
  ,"datacenter": "place6"
   ,"disable_remote_exec": true
  ,"disable_update_check": true
   ,"encrypt": "xx=="
   "retry_join": ["black1.place6.ungleich.ch", "black2.place6.ungleich.ch", "black3.place6.ungleich.ch",
[13:06] router1.place6:/etc/consul# consul --version
Consul 1.6.2
Protocol 2 spoken by default, understands 2 to 3 (agent will automatically use protocol >2 when speaking to co
mpatible agents)
[13:06] router1.place6:/etc/consul#
```

Seem like old bind_addr now supports interfaces - much nicer!

• See https://www.consul.io/docs/agent/options.html

```
[13:25] router1.place6:/etc/consul# /etc/init.d/consul restart
* Stopping consul ...
* Checking /etc/consul ...
Config validation failed: Multiple private IPv4 addresses found. Please configure one with 'bind' and/or 'adve
rtise'.
                                                                                                 [ ! ! ]
* Starting consul ...
                                                                                                    [ ok ]
[13:25] router1.place6:/etc/consul# mv conf.d/*json .
[13:25] router1.place6:/etc/consul# /etc/init.d/consul restart
* Stopping consul ...
* Checking /etc/consul ...
Configuration is valid!
                                                                                                     [ ok ]
 Starting consul ...
[13:25] router1.place6:/etc/consul#
```

However it does not work -- at the moment hard coded to the routers ipv6 address. Also the conf.d change does not seem to work.

#3 - 01/18/2020 01:27 PM - Nico Schottelius

- Subject changed from Manually fix consul on new router1.place6 to Manually fix consul+node_exporter on new router1.place6

#4 - 01/18/2020 01:35 PM - Nico Schottelius

```
[13:30] router1.place6:/etc/consul# consul members

Error retrieving members: Get http://127.0.0.1:8500/v1/agent/members?segment=_all: dial tcp 127.0.0.1:8500: co
nnect: connection refused
[13:30] router1.place6:/etc/consul# netstat -anp | grep consul
```

Seems to crash when running under supervise (probably permission error):

```
Jan 18 13:31:36 router1 daemon.info supervise-daemon[15251]: Child command line: /usr/sbin/consul agent -config-dir=/etc/consul

Jan 18 13:31:36 router1 daemon.info supervise-daemon[15323]: Supervisor command line: supervise-daemon consul
--start --stdout /var/log/consul.log --stderr /var/log/consul.log --pidfile /run/consul.pid --respawn-delay 10
--respawn-max 0 --healthcheck-timer 60 --user cons

Jan 18 13:31:36 router1 daemon.info supervise-daemon[15325]: Child command line: /usr/sbin/consul agent -confi
```

04/25/2024 2/3

```
g-dir=/etc/consul
Jan 18 13:31:36 router1 daemon.warn supervise-daemon[15324]: /usr/sbin/consul, pid 15325, exited with return c ode 1
Jan 18 13:31:46 router1 daemon.info supervise-daemon[15353]: Child command line: /usr/sbin/consul agent -config-dir=/etc/consul
Jan 18 13:31:47 router1 daemon.warn supervise-daemon[15324]: /usr/sbin/consul, pid 15353, exited with return c ode 1
Jan 18 13:31:49 router1 auth.info sshd[15231]: Connection closed by 123.207.78.83 port 44658 [preauth]
Jan 18 13:31:49 router1 auth.notice sshguard[4977]: Attack from "123.207.78.83" on service SSH with danger 2.
Jan 18 13:31:50 router1 daemon.warn bird: I/O loop cycle took 5291 ms for 1 events
Jan 18 13:31:57 router1 daemon.info supervise-daemon[15375]: Child command line: /usr/sbin/consul agent -config-dir=/etc/consul
Jan 18 13:31:57 router1 daemon.warn supervise-daemon[15324]: /usr/sbin/consul, pid 15375, exited with return c ode 1
```

#5 - 01/18/2020 01:35 PM - Nico Schottelius

- Description updated

#6 - 12/07/2021 12:52 AM - Nico Schottelius

- Status changed from In Progress to Rejected

04/25/2024 3/3